



**PHITAOS**  
THE ART OF STONE

TECHNICAL DATA SHEET

## HENRI IV MARBLE



### Nature

Secondary cretaceous Era,  
Urgonien Stratum

### Aspect

Grey uniform background  
with fine to extremely fine  
grain texture with fossils and  
small shells

### Origin

France

## TECHNICAL CHARACTERISTICS

<b>Apparent Density</b>	2709 kg/m <sup>3</sup>	NF EN 1936
<b>Porosity per volume</b>	0,15%	NF EN 1936
<b>Sound velocity</b>	6470 m/s	NF EN 14579
<b>Compressive Strength</b>	143,8 Mpa	NF EN 1926
<b>Bending Strength</b>	18,5 Mpa	NF EN 12372
<b>Abrasion Resistance</b>	average 2 mm	NF EN 14157
<b>Frost resistance</b>	more than 240 cycles Frost resistant stone	NF EN 12371

### Recommended uses

*Walls & Floor  
Decorative*

External & Internal for heavy traffic usage  
Fireplace, column, mouldings, ...

### Possible finishes

Rough, honed, brush, polished, tooled,  
hammered, sand-blasted, ...

**PHITAOS**  
THE ART OF STONE

#### Head quarter

28, Blvd de Bonne Nouvelle - 75010 PARIS - FRANCE  
SARL au Capital de 7500 Euros  
SIREN 522 015 304 RCS PARIS - n° TVA FR33522015304

Tel : + 331 4246 3507

Fax : + 339 5602 7494

[Information@phitaos.com](mailto:Information@phitaos.com)

[www.phitaos.com](http://www.phitaos.com)